



Electric four wheel counterbalance forklift truck

CBH 2.5-3.0

Lift height: 3300-4800 mm / Load capacity: 2500-3000 kg

CBH 2.5-3.0

Trucks that simply work.

Built for use in changing environments.

The AntOn by Jungheinrich CBH electric forklift truck combines what counts for daily operation: robust technology, easy handling and reliable performance.

Whether in the warehouse, outdoors or at the loading ramp: the CBH is versatile and delivers exactly where it is needed. This electric forklift truck will always make your job easier – from internal transport, manoeuvrable applications in confined spaces and the rapid loading and unloading of HGVs.

It excels not only in daily use but also through its fast availability and a price/performance ratio that makes transitioning to electromobility particularly appealing.

With three carefully designed equipment variants and advanced lithium-ion power, the CBH offers exactly the flexibility your company needs today, making the choice easy – a forklift truck that simply works.

All benefits at a glance

- Reliable technology for everyday use.
- Three equipment variants for a wide range of requirements.
- Simple operation for comfortable handling.
- Lithium-ion technology for fast charging and consistent performance.
- High availability for fast delivery.

Versatile

Functional power for every job.

- Two capacity options, each available in three equipment variants to match different applications, needs and budgets.
- Compact and highly manoeuvrable – even in tight spaces.
- Large tyres and high ground clearance for outdoor use on uneven ground.
- Flexible charging options via an external or built-in charger, depending on the model.
- Travel speeds up to 17 km/h for more efficient working.

Straightforward

Intuitive technology that makes work easier.

- LED display with all key info at a glance.
- Simple control elements – from the control panel and comfortable pedal to the water-resistant charging port.
- Optimum visibility for safer daily operation.
- Ergonomic operator position with adjustable steering wheel and, depending on the variant, comfort seat and generous legroom.

Cost-effective

Solutions for every task and every budget.

- Maintenance-free 80-V lithium-ion battery for long service life and short charging pauses.
- Rapid lift speeds save time with every application.
- High availability and cost-efficient acquisition.
- Fast spare parts supply keeps your operations running smoothly.

Masts

CBH 2.5 (V1: ZT3300, ISS, ZH1)	Lift (h3)	Retracted mast height (h1)	Free lift (h2)	Extended mast height (h4)	Forward/backward tilt of fork carriage
Duplex mast ZT	3300 mm	2240 mm	195 mm	4360 mm	6 / 10 °
CBH 2.5 (V2: DZ4800, ISS, ZH2, Eco1), CBH 2.5 (V3: DZ4800, ASS, ZH2, Com3)	Lift (h3)	Retracted mast height (h1)	Free lift (h2)	Extended mast height (h4)	Forward/backward tilt of fork carriage
Triplex mast DZ	4800 mm	2265 mm	1240 mm	5895 mm	6 / 6 °
CBH 3.0 (V1: ZT3300, ISS, ZH1)	Lift (h3)	Retracted mast height (h1)	Free lift (h2)	Extended mast height (h4)	Forward/backward tilt of fork carriage
Duplex mast ZT	3300 mm	2215 mm	135 mm	4430 mm	6 / 10 °
CBH 3.0 (V2: DZ4800, ISS, ZH2, Eco1), CBH 3.0 (V3: DZ4800, ASS, ZH2, Com3)	Lift (h3)	Retracted mast height (h1)	Free lift (h2)	Extended mast height (h4)	Forward/backward tilt of fork carriage
Triplex mast DZ	4800 mm	2265 mm	1170 mm	5975 mm	6 / 6 °

VDI table

Characteristic	1.1	Manufacturer (abbreviated description)			Jungheinrich
	1.2	Manufacturer's type designation			CBH 2.5-3.0
	1.3	Drive type			electric
	1.4	Operation			Seat
	1.5	Load capacity/load	Q	kg	2500
	1.6	Load centre distance	c	mm	500
	1.8	Load distance, centre of drive axle to fork	x	mm	495
	1.9	Wheelbase	y	mm	1740
Weights	2.1.1	Service weight (incl. battery)		kg	3977
	2.2	Axle load laden front/rear		kg	5795 / 682
	2.3	Axle load unladen front/rear		kg	1865 / 2112
Wheels/chassis	3.1	Tyres			Super-elastic (SE)
	3.2	Tyre size, front			7.00-12
	3.3	Tyre size, rear			18x7-8
	3.5	Wheels, number front/back (x=driven)			2x / 2
	3.6	Tread width, front	b10	mm	975
	3.7	Tread width, rear	b11	mm	955
Basic dimensions	4.1	Forward/backward tilt of mast	a/β	°	6 / 10
	4.2	Retracted mast height (h1)	h1	mm	2090
	4.3	Free lift (h2)	h2	mm	120
	4.4	Lift (h3)	h3	mm	3000
	4.5	Extended mast height (h4)	h4	mm	4025
	4.7	Height of overhead guard (cab)	h6	mm	2165
	4.8	Seat height/stand height	h7	mm	1095
	4.12	Coupling height	h10	mm	311
	4.19	Total length	l1	mm	3695
	4.20	Length including fork shank	l2	mm	2545
	4.21.1	total width	b1	mm	1154
	4.22	Fork dimensions	s/e/l	mm	40 x 122 x 1150
	4.23	Fork carriage connection class			2A
	4.24	Fork carriage width	b3	mm	1040
	4.31	Ground clearance laden under mast	m1	mm	125
	4.32	Ground clearance centre of wheelbase	m2	mm	170
	4.34.1	Aisle width (pallet 1000×1200 sideways)	Ast	mm	3995
	4.34.2	Aisle width (pallet 800x1200 length)	Ast	mm	4195
	4.35	Turning radius	Wa	mm	2300
	4.36	Smallest pivot point distance	b13	mm	838
Performance data	5.1	Travel speed laden/unladen		km/h	16 / 17
	5.2	Lift speed laden/unladen		m/s	0.5 / 0.56
	5.3	Lowering speed laden/unladen		m/s	0.54 / 0.56
	5.5	Drawbar pull laden/unladen		N	2270 / 2270
	5.6	Max. drawbar pull laden/unladen		N	13760 / 13760
	5.7	Gradeability laden/unladen		%	14 / 25
	5.8	Max. gradeability laden/unladen		%	20 / 25
	5.9	Acceleration time laden/unladen		s	6.6 / 6.4
	5.10	Service brake			hydraulic

Electric motor/electronics	6.1	Drive motor, performance S2 60 min	kW	17
	6.2	Lift motor, performance with S3	kW	26
	6.4	Battery voltage/nominal capacity	V / Ah	80 / 230
	6.6.1	Energy consumption according to EN cycle	kWh/h	7.1
	6.6.2	CO2 equivalent as per EN 16796	kg/h	3.8
	6.7	Throughput	t/h	150
	6.8.1	Energy consumption with max. throughput	kWh/h	6.21
Other	8.1	Type of drive control		AC
	10.1	Operating pressure for attachment	bar	180
	10.2	Oil flow for attachments	l/min	35
	10.7	Sound pressure level according to EN12053	dB (A)	74

- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.

VDI table

Characteristic	1.1	Manufacturer (abbreviated description)		Jungheinrich
	1.2	Manufacturer's type designation		CBH 2.5-3.0
	1.3	Drive type		electric
	1.4	Operation		Seat
	1.5	Load capacity/load	Q kg	3000
	1.6	Load centre distance	c mm	500
	1.8	Load distance, centre of drive axle to fork	x mm	481
	1.9	Wheelbase	y mm	1740
Weights	2.1.1	Service weight (incl. battery)	kg	4335
	2.2	Axle load laden front/rear	kg	6575 / 760
	2.3	Axle load unladen front/rear	kg	1880 / 2455
Wheels/chassis	3.1	Tyres		Super-elastic (SE)
	3.2	Tyre size, front		28x9-15
	3.3	Tyre size, rear		200/50-10
	3.5	Wheels, number front/back (x=driven)		2x / 2
	3.6	Tread width, front	b10 mm	1010
	3.7	Tread width, rear	b11 mm	955

Basic dimensions	4.1	Forward/backward tilt of mast	a/β	°	6 / 10
	4.2	Retracted mast height (h1)	h1	mm	2070
	4.3	Free lift (h2)	h2	mm	135
	4.4	Lift (h3)	h3	mm	3000
	4.5	Extended mast height (h4)	h4	mm	4095
	4.7	Height of overhead guard (cab)	h6	mm	2180
	4.8	Seat height/stand height	h7	mm	1110
	4.12	Coupling height	h10	mm	307
	4.19	Total length	l1	mm	3712
	4.20	Length including fork shank	l2	mm	2562
	4.21.1	total width	b1	mm	1210
	4.22	Fork dimensions	s/e/l	mm	45 x 122 x 1150
	4.23	Fork carriage connection class			3A
	4.24	Fork carriage width	b3	mm	1100
	4.31	Ground clearance laden under mast	m1	mm	130
	4.32	Ground clearance centre of wheelbase	m2	mm	185
	4.34.1	Aisle width (pallet 1000×1200 sideways)	Ast	mm	4060
	4.34.2	Aisle width (pallet 800x1200 length)	Ast	mm	4260
	4.35	Turning radius	Wa	mm	2379
	4.36	Smallest pivot point distance	b13	mm	838
Performance data	5.1	Travel speed laden/unladen		km/h	16 / 17
	5.2	Lift speed laden/unladen		m/s	0.42 / 0.5
	5.3	Lowering speed laden/unladen		m/s	0.43 / 0.44
	5.5	Drawbar pull laden/unladen		N	2770 / 2770
	5.6	Max. drawbar pull laden/unladen		N	16280 / 16280
	5.7	Gradeability laden/unladen		%	12 / 23
	5.8	Max. gradeability laden/unladen		%	20 / 25
	5.9	Acceleration time laden/unladen		s	6.7 / 6.3
	5.10	Service brake			hydraulic
Electric motor/electronics	6.1	Drive motor, performance S2 60 min		kW	17
	6.2	Lift motor, performance with S3		kW	26
	6.4	Battery voltage/nominal capacity		V / Ah	80 / 230
	6.6.1	Energy consumption according to EN cycle		kWh/h	10.73
	6.6.2	C02 equivalent as per EN 16796		kg/h	5.8
	6.7	Throughput		t/h	180
	6.8.1	Energy consumption with max. throughput		kWh/h	10.01
Other	8.1	Type of drive control			AC
	10.1	Operating pressure for attachment		bar	180
	10.2	Oil flow for attachments		l/min	35
	10.7	Sound pressure level according to EN12053		dB (A)	74

- This data sheet according to VDI guideline 2198 only states the technical values of the standard truck. Different tyres, other masts, additional equipment etc. may result in different values.

Appendix

